

23.9.1986	Übergänge f. Linkspülbohren und Trockenbohren	08.00.01	
Übergänge für Linkspülbohren (HGN)			
Anschlüsse/Nennweite	Außendurchmesser (mm)	Länge (mm)	Masse (kg)
3 1/2" SN-M x 2 7/8" IF-M 4 1/2" Ssoh-M x 2 7/8" IF-M 4 1/2" Ssoh-M x 4 1/2" IF-M (FL-LK160) ^x 6 5/8" Ssoh-M x 4 1/2" IF-M (FL-LK160/240) ^x 6 5/8" Ssoh-Z x 4 1/2" IF-M (FL-LK240) ^x 6 5/8" SN-M x 4 1/2" IF-M (FL-LK160) ^x S-63,5-M x 2 7/8" IF-M 4 1/2" IF-Z x 2 7/8" IF-M 4 1/2" IF-Z x FL-LK150 4 1/2" IF-Z x FL-LK330 2 7/8" IF-Z x FL-LK150 FL-LK160 x 4 1/2" IF-M ^x FL-LK240 x FL-LK160 ^x 4 1/2" IF-Z x FL-LK160 ^x FL-LK160 x FL-LK150 ^x FL-LK240 x 4 1/2" IF-M ^x	194 194 194 194 280 194 194 200 200 400 200 200 200 280 280 200 280	400 400 400 500 500 500 400 400 510 330 1500 500 500 335 1500 580	23 27 63 79 63 72 20 27 28 50 26 35 26 33 32 44
^x Einsatz nur noch seitlich begrenzt			
Übergänge für Trockenbohren (SHK)			
Bezeichnung	Anschlüsse	Schlüsselweite (mm)	
Übergangsmuffe Gestängeübergang Gestängeübergang Gestängeübergang	2 1/2" r M x 2" r M 2 1/2" r V x 2" r M 2 1/2" r M x 2" r V 2" l V x 2" r M	 65 65	
Tabellen Bohrtechnik			